

### Print carrier

### Average values

**JAC® Metallic** is a series of paper-laminated foils available in a variety of colour shades. They are used for the manufacture of high-quality labels and stickers, e. g. corporate emblems, nameplates on machines and kit chen appliances, quality seals etc., and for the labeling of up-market cosmetic products.

**JAC® Metallic** is suitable for all (**excluding digital print**) printing processes (special printing inks are required for letterpress and offset).

52060 – silver, matt  
52160 – silver, gloss

	52060	52160
Weight (g/m <sup>2</sup> )	81	83
Thickness (micron)	66	66
Shelf life of laminate (years) <sup>1</sup>	2	2

<sup>1</sup> Stored in original packaging a temperature of 22 ± 2°C and a relative humidity of 50% ± 5%

For technical guidance please visit our website under please visit our website under downloads "Guidelines for Use" - Offset printing.

### Adhesive

### Average values

#### DURO D2010

A general purpose permanent, acrylic based adhesive. The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.

#### DURO D2010

Adhesion (N/25 mm) (FTM2 on st. steel/20 min. bond time)	9
Tack (N/25 mm) (FTM9 on glass)	16
Recommended minimum application temperature (°C)	>+5
Service temperature (°C)	-20
Resistance to cold (°C) <sup>2</sup>	+80

<sup>2</sup> Not fully resistant until after adhesion reaches full strength – after at least 24 hrs

For information regarding EHS regulation please visit our web side under downloads "Guidelines for Use" 5.12 Product Compliance Jac Screen.

### Silicone paper

### Average values

**B 80** – siliconized kraft, wood-free, special-purpose paper, moisture-stabilized through a special coating on one side. It displays high dimensional stability and excellent flatness.

	B 80
Weight (g/m <sup>2</sup> )	82
Thickness	79

Issue May 2021

#### Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>

JAC® is registered trademark of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.